



ANSI B 29.4 Outer attachments for American series

Base Chain Model	Chain No	Pitch (P)	Thickness (t)	M	d	D	C	P1
C 2040	32-A 08A 01 K2 01	25.40	1.50	19.10	3.33	12.70	9.12	9.52
C2042								
C2050	32-A 102 01 SK2	31.75	2.00	23.80	5.08	15.83	11.13	11.91
C2052								
C2060	32-A 121 01 SK2	38.10	2.39	28.60	5.08	21.44	14.68	14.30
C2062								
C2060H	32-A 122 01 K2 01	38.10	3.15	28.60	5.08	21.44	14.68	14.30
C2062H								
C2080	32-A 161 01 K2 01	50.80	3.15	38.10	6.63	27.79	19.05	19.05
C2082								
C2080H	32-A 162 01 K2 05	50.80	4.00	38.10	6.63	27.79	19.05	19.05
C2082H								
C2100	32-A 201 01 K2 01	63.50	4.00	47.60	8.20	33.32	23.42	23.83
C2102								
C2100H	32-A 202 01 K2 01	63.50	4.70	47.60	8.20	33.32	23.42	23.83
C2102H								
C2120	32-A 241 01 K2 01	76.20	4.70	57.20	9.80	39.67	27.79	28.58
C2122								
C2120H	32-A 242 01 K2 01	76.20	5.56	57.20	9.80	39.67	27.79	28.58
C2122H								
C2160	32-A 321 01 K2 01	101.60	5.56	76.20	13.11	52.37	36.53	38.10
C2162								
C2160H	32-A 322 01 K2 01	101.60	7.14	76.20	13.11	52.37	36.53	38.10
C2162H								

A2 - Attachment on One side
K2- Attachment on Both sides

Note : Please select the required attachment either A2 or K2 and specify the frequency of attachments while ordering