



DIN 8187-2 Outer Attachments for European Series

Base Chain Model	ATT. No.	P	T	d	M	N	H
08B	42 D 083 01 M2 00	12.586	1.58	4.50	23.22	13.00	18.42
10B	42 D 101 01 M2 00	15.77	1.58	5.30	29.31	16.50	23.10
12B	42 D 120 01 M2 00	18.91	1.81	6.60	32.99	21.00	28.43
16B	42 D 160 01 M2 00	25.235	3.05	6.60	45.90	23.00	36.64
20B	42 D 200 01 M2 00	31.75	3.53	9.00	58.04	30.50	42.00

ANSI B29.1 Outer Attachments for American Series

Base Chain Model	ATT. No.	P	T	d	M	N	H
40	31 D 08A 01 M2 02	12.586	1.50	4.20	23.22	12.70	19.24
50	31 D 102 01 M2 03	15.77	2.00	5.10	29.31	15.88	24.20
60	31 D 121 01 M2 01	19.05	2.39	5.10	34.87	19.05	26.70
80	31 D 161 01 BM2 1A	25.247	3.15	6.60	45.90	25.40	36.64
100	31 D 201 01 M2 01	31.75	4.00	8.21	56.69	31.75	42.00
120	31 D 241 01 M2 01	38.10	4.70	9.81	68.71	36.53	52.55
140	31 D 281 01 M2 01	44.45	5.50	11.38	80.52	44.50	64.32
160	31 D 321 01 M2 01	50.80	6.30	13.11	91.44	50.80	68.15

Work Standard Outer Attachments for European Series

Base Chain Model	ATT. No.	P	T	d	M	N	H
06B	31 D 061 01 M2 00	9.45	1.00	3.50	17.60	9.50	13.41
08B	31 D 083 01 M2 02	12.586	1.58	4.30	23.22	14.40	18.34
10B	31 D 101 01 M2 01	15.77	1.58	5.20	29.31	15.90	24.70
12B	31 D 120 01 M2 02	18.91	1.81	5.60	32.99	17.90	31.28
16B	31 D 160 01 M2 02	25.235	3.05	6.80	45.90	26.00	36.64

SM2 - Attachment on single side.

M2 - Attachment on both sides.

Note : Please select the required attachment either SM2 or M2 and specify the frequency of attachment while ordering.