



- * These chains are designed to face special needs in wood, tile, glass, carton printing, PVC tube extrusion industries.
- * The rubber attachment can be supplied with precision single or duplex roller chains
- * Special Profiles can be made on request

- * These chains are designed to face special needs in wood, tile, glass, carton printing, PVC tube extrusion industries.
- * The rubber attachment can be supplied with precision single or duplex roller chains
- * Special Profiles can be made on request

Grade	Natural Rubber	Nitrile Rubber	Neoprene Rubber
SHORE HARDNESS (A)	65+/-5	65+/-5	65+/-5
TEMPERATURE RANGE	- 10 to + 70 deg c	- 10 to + 120 deg c	- 10 to + 80 deg c
RESISTANCE TO OIL/GREASE	POOR	EXCELLENT	FAIR
OZONE / UV RESISTANCE	POOR	FAIR	EXCELLENT

Intl. Ref. No.	Chain No.	Type	Pitch (P)	Width Over Bearing Pin (A)	C	H	h	L	S	Tensile Strength (KN) (Min)
08B-1	D08301RT01	A	12.70	17.80	8.30	12.30	14.72	24.00	1.50	32.07
80-1	D16101RT01	A	25.40	38.00	18.30	23.00	27.50	49.40	3.15	32.26
08B-2	D08302RT01	B	12.70	33.90	9.50	18.30	44.00	24.00	1.50	18.04
08B-2	D08302RT02	A	12.70	33.90	9.50	12.50	28.50	24.00	1.50	62.37
60-2	D12102RT01	C	19.05	53.00	11.80	33.80	45.56	34.87	2.00	55.60